

	BUCCIATO LUCIDO	SPECIFICATIONS
		Rev. 0 – Ed. 1

SPECIFICATIONS AND FIELDS OF EMPLOYMENT

A gloss continuous wall covering for interiors, BUCCIATO LUCIDO can be applied over any other product, producing a glossy “orange peel”-like effect. BUCCIATO LUCIDO can be easily washed and is highly resistant to mechanical stresses and washings; for these reasons, it is ideal for hospitals, schools or public premises in general, where an absolute hygiene is needed.

COMPOSITION

BUCCIATO LUCIDO is a synthetic-resin-based product in paste in water emulsion, containing titanium and/or iron oxides and specific additives. It does not contain any noxious substance such as lead or chrome-based pigments and solvents.

METHODS OF APPLICATION

Thin plaster or plasterboard supports and old water paints if previously treated and completely dry and cohesive, are suitable bases for the product.

Do not apply on supports that clearly present infiltrating or resurfacing humidity.

First of all, sand, dust and plaster over all the imperfections with STUCCOMURO or POLISTUCK (depending on the thickness of the imperfections); then put on a coat of FISSATIVO UNIVERSALE opportunely diluted in water from a ratio of 1 to 2 to a ratio of 1 to 6, according to the absorption degree of the support; after 12 hours, put on, with a bristle roller, a first coat of BUCCIATO LUCIDO as primer diluted in 25% of water.

After at least three hours, put on the second coat of BUCCIATO LUCIDO diluted in maximum 5% of water using a sponge roller.

TECHNICAL DATA

SPECIFIC WEIGHT:	1150 grams/litres +/- 5%
VISCOSITY:	thixotropic paste
DRYING:	dry to the touch: about 2 hours at 20°C completely dry: about 24 hours at 20°C
TEMPERATURE OF APPLICATION:	between 5°C and 30°C
YIELD:	0,450 – 0,550 litres/m ² (with two coats)
COLOURS:	to be chosen in the catalogue
PACKAGE:	13 / 5 / 2,5-litres polyethylene cases available
PRESERVATION:	18 months in the intact packages, away from temperature changes

ITEM OF SPECIFICATIONS

Decoration and protection of internal surfaces with synthetic wall covering and a glossy “orange peel”-like effect, like BUCCIATO LUCIDO, the synthetic resin-based material in water emulsion, containing titanium and/or iron oxides and specific additives, produced by Spiver Ltd.; previous application of a coat of FISSATIVO UNIVERSALE, opportunely diluted in water from a ratio of 1 to 2 to a ratio of 1 to 6, according to the absorption degree of the support; apply, with a bristle roller, a first coat of BUCCIATO LUCIDO as primer diluted in 25% of water and, after at least three hours, put on, with a sponge roller, the second coat of BUCCIATO LUCIDO diluted in maximum 5% of water.

Price inclusive of the material and implementation, except the scaffoldings per square metre: £.....

N.B. The above-mentioned data are susceptible of variations. Spiver Ltd. is not responsible for any negative result depending on the application of the product out of the Company's control and on the agents unrelated to the product quality.