

	SPIVERQUARTZ GRAFFIATO	SPECIFICATIONS
		Rev. 0 – Ed. 1

SPECIFICATIONS AND FIELDS OF EMPLOYMENT

A synthetic-resin-based paint, it is employed as continuous wall covering for exteriors. In the building industry, it is employed for the protection and decoration of both external and internal walls of modern or old buildings. Thanks to the type of emulsion employed, SPIVERQUARTZ GRAFFIATO has high water-repellent properties and therefore it is successfully employed in particularly harsh surroundings (such as seaside areas or industrial plants). Moreover, SPIVERQUARTZ GRAFFIATO has high impermeability levels and, for this reason, it is particularly suitable for the protection and decoration of external thermal composite systems as coloured finishing.

COMPOSITION

SPIVERQUARTZ GRAFFIATO is a synthetic-resin compound in paste in water emulsion and contains selected inert elements, light-resistant and weatherproof pigments and specific additives.

METHODS OF APPLICATION

Fine lime and/or cement-based mortar supports, spurious mortars, mineral or synthetic paintings and coverings (if completely dry and cohesive), are suitable for the product.

Apply a coat of DERASOL diluted in turpentine in the ratio of 1 to 1; after 12 hours, put on a coat of SPIVERQUARTZ LISCIO as a sealer diluted in 40% of water of the chosen colour.

Spread SPIVERQUARTZ GRAFFIATO with an iron float and finish off with a plastic float. Do not apply on supports that clearly present infiltrating or resurfacing humidity.

TECHNICAL DATA

SPECIFIC WEIGHT:	1840 grams/litres +/- 5%	
VISCOSITY:	thixotropic paste	
DRYING:	dry to the touch:	about 4 hours at 20°C with a relative humidity below 60%
	completely dry:	about 48 hours at 20°C with a relative humidity below 60%
TEMPERATURE OF APPLICATION:	between 5°C and 30°C	
YIELD:	MEDIUM (2 millimetres)	- 0,440 – 0,500 litres/m ² consumption
	FINE (1,5 millimetres)	- 0,600 – 0,625 litres/m ² consumption
COLOURS:	to be chosen in the catalogue	
PACKAGE:	16-litres polyethylene cases available	
DILUTION:	ready to use	
PRESERVATION:	24 months in the intact packages, away from temperature changes	

ITEM OF SPECIFICATIONS

Decoration and protection of internal and external surfaces with synthetic parget, like SPIVERQUARTZ GRAFFIATO, the synthetic resin-based paint in water emulsion containing selected inert elements, light-resistant and weatherproof pigments and specific additives, produced by Spiver Ltd.; prior setting treatment with a coat of DERASOL produced by Spiver Ltd., diluted in turpentine in the ratio of 1 to 1 and prior application of a coat of SPIVERQUARTZ LISCIO as a sealer, diluted in 40% of water of the chosen colour.

Price inclusive of the material and implementation, except the scaffoldings per square metre: £.....

N.B. The above-mentioned data are susceptible of variations. Spiver Ltd. is not responsible for any negative result depending on the application of the product out of the Company's control and on the agents unrelated to the product quality.

